

## Quality - PE610/FR

### Description

#### **610gsm PVC Coated Polyester, Matt Finish, FR**

This quality is flame retardant and meets the requirements of BS7837:1996, which assesses the flammability performance of textiles used in the construction of marquees and structures. This quality is generally used for tarpaulin and cover applications where a flame retardant material is demanded.

### Product Details

Roll sizes (nominal)	150cm x 50m	205cm x 50m
Finish	Matt	
Standard Colours	Blue Orange Black White Yellow Red Olive Green Grey <b>Dark Grey</b>	Blue Black White Green Red <b>Sand</b>
<b>END OF LINE COLOURS</b>	Navy Blue	

### Technical Data

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	Flexible PVC both sides	
Total Weight	610gsm	
Tensile Strength	Warp - 2,300 N/50mm Weft - 2,200 N/50mm	EN ISO 1421
Tear Strength	Warp - 230 N Weft - 200 N	DIN 53356
Coating Adhesion	80 N/50mm	DIN 53357
Temp Resistance	-25 to +60 Deg C	
Fire Behaviour	Pass	BS7837:1996

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251