Issue Date: 01.08.2024



Quality - PW900 (B6000)

Description

900gsm PVC Coated Polyester with Gloss and Lacquered Finish

900gsm PVC coated panama weave polyester. This quality is produced with a high gloss finish and an acrylic lacquer applied to both sides. Mainly used for fabricating side curtains for trucks or heavy weight tarpaulins where higher strength is required.

Product Details

		T				
Roll sizes (nominal)	300cm x 58m	300cm x 30m				
Finish	Gloss with lacquer both sides					
All colours available in 58m rolls as standard. Colours marked * also available in						
30m rolls.						
Yellow (1001)*	Blue (5003)	Green (6027)				
Tan (1003)	Blue (5004)	Green (6028)				
Yellow (1018)*	Mid Blue (5007)*	Brilliant Green (6036)				
Yellow (1021)	Blue (5020)	Brunswick Green (6037)*				
Yellow (1024)	Ice Blue (5023)	Pea Green (6038)				
Yellow (1025)	Pacific Blue (5025)	Bottle Green (6039)*				
Yellow (1059)	French Blue (5026)*	Grey (7001)				
Cream (1622)	Blue (5027)	Old Ford Grey (7002)				
Devon Cream (1623)	Ultra Blue (5028)	Grey (7003)				
Truck Red (3001)*	Bright Blue (5029)	Charcoal Grey (7024)*				
Juniper Red (3002)	J.P. Blue (5030)	Silver Grey (7060)				
Red (3015)	Blue (5031)	Dove Grey (7071)				
Flame Red (3016)	Oxford Blue (5032)*	Grey (7179)				
Maroon (3017)	Dark Blue (5033)	Grey (7244)				
Int. Orange (3018)*	Blue (5061)	Grey (7340)				
Orange (3021)	Blue (5063)	Silver (7500)				
Orange (3056)	Blue (5104)	Black (7999)				
Dark Maroon (3057)	Aircraft Blue (5158)	Brown (8020)				
Red (3105)	Green (6001)*	White (9002)				
Blue (5001)	Green (6002)	White (9013)				

Tel: 01382 229251

Issue Date: 01.08.2024



Quality - PW900 (B6000)

Technical Data

Parameter	Result	Test Method	
Base Cloth	Polyester		
Coating	Flexible PVC both sides		
Finish	Acrylic Lacquer Both Sides		
Total Weight	900gsm		
Tensile Strength	Warp - 4,000 N/50mm	EN ISO 1421	
	Weft - 4,000 N/50mm		
Tear Strength	Warp - 600 N	DIN 53363	
	Weft - 500 N		
Coating Adhesion	100 N/50mm	DIN 53357	
Temperature	-30 / +70 Deg C	DIN EN ISO 1876-2	
Resistance			
Fire Behaviour	<100mm/min	ISO 3795	

Additional Information

This quality is also available in 320cm wide as standard in Blue (5031), Grey (7003), Silver (7500) and White (9002). For special order, 320cm can also be produced in any colour subject to an MOQ of 1,000LM.

PW900 can also be supplied in slit rolls to customer requirement providing that a full 300cm x 58m rolls is ordered when slit. Slitting is subject to an additional charge and lead time. Please contact us to discuss your requirements.

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

Tel: 01382 229251