



**Quality - PE550FL Fluorescent PVC**

**Description**

**550gsm PVC coated Polyester, matt finish, Fluorescent**

This quality is stocked in fluorescent orange and yellow. It has the same fluorescent coating on both sides, which sets it apart from some other fluorescent qualities on the market. Fluorescent pigments have a limited colour fastness when exposed to UV, but the PVC coating will remain in tact after.

**Product Details**

Roll sizes (nominal)	150cm x 50m	205cm x 50m
Finish	Matt	
Standard Colours	Flouro Orange (9049)	Flouro Orange (9049) Flouro Yellow (9062)
	<i>See Note on Pigments on TDS</i>	

**Technical Data**

Parameter	Result	Test Method
Base Cloth	HT Polyester	
Coating	Flexible PVC both sides	
Total Weight	550gsm	
Tensile Strength	Warp - 2,500 N/50mm Weft - 1,800 N/50mm	EN ISO 1421
Tear Strength	Warp - 250 N Weft - 250 N	DIN 53363
Coating Adhesion	90 N/50mm	EN ISO 2411
Temperature Resistance	-30/+70 Deg C	DIN EN 1876-2
Fire Behaviour	<100mm/min	ISO3795
NOTE		

All Technical Data is indicative.  
Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251

